



GENERAL NOTES:

1. FOR PARALLEL PIPES (CULINARY AND IRRIGATION) THE DISTANCES MINIMUM BETWEEN PIPES SHALL BE 5'-0" HORIZONTAL AND 4" VERTICAL. (IRRIGATION LINE ON TOP) SEE STANDARD DRAWING NO 503
2. PIPE SHALL BE "BLUE" FOR CULINARY WATER, "PURPLE" FOR PRESSURIZED IRRIGATION, AND "WHITE" OR "GREEN" FOR SEWER.
3. NO PRESSURIZED UTILITIES INSTALLED PARALLEL TO ANOTHER PRESSURIZED UTILITY MAY BE INSTALLED CLOSER THAN 5' (EDGE TO EDGE) TO SAID UTILITY.
4. NO CULINARY WATER/PRESSURIZED IRRIGATION CROSS-CONNECTIONS SHALL BE ALLOWED.
5. ALL PRESSURIZED IRRIGATION LINES SHALL BE "LAID TO GRADE" IN ORDER TO DRAIN P.I. LINES WHEN NOT IN USE.
6. IN THE EVENT THE NATIVE EXCAVATED MATERIAL IS NOT SATISFACTORY FOR BACKFILLING AS BY THE TOWN ENGINEER OR THE PUBLIC WORKS DEPARTMENT, THE CONTRACTOR SHALL PROVIDE AN IMPORTED GRANULAR MATERIAL TO MEET THE SPECIFICATIONS OUTLINED IN SECTION 7.12 OF THE CITY OF CEDAR HILLS DESIGN STANDARDS AND PUBLIC IMPROVEMENTS SPECIFICATIONS.
7. PEA GRAVEL SHALL NOT BE ACCEPTED AS A BEDDING OR BACKFILL MATERIAL.
8. ALL CONCRETE COLLARS WITHIN DISTURBED AREAS SHALL BE REMOVED PRIOR TO PAVING. COLLARS SHALL THEN BE REPLACED AFTER PAVING IS COMPLETE.



**CEDAR HILLS**

STANDARD  
DRAWING NO.

502

**UTILITY INSTALLATION  
AND ROAD REPAIR**